

RoHS

Country of Origin : China

Operating Temperature : 0 ÷ 40 [°C]

Dimension : 116 x 49 x 39 [mm]

Car adapter DC-DC convertor

Approvals / Marks : 



### Features:

Car adapter for notebook can be used in a cars and trucks.

Wide range Input (11 ~ 28)Vdc.

Output current & output Voltage protection.

Power ON LED.

This model is for ASUS EEE notebooks.

For I.T.E. use only + RoHS conform.

### Specification:

		OUTPUT						
	Model	Voltage DC [V]	Loading [A]	Tol. [V]	Efficiency [%]	Max. Power [W]	Ripple & Noise [mV]p-p	Connector [mm]
	STXX-1505-CUV	5	0~3.0	±0.5	82	15	200	2.1x5.5x11
	STAS-3612-CUV	12	0~3.0	±0.5	82	36	200	1.7x4.8x11
	STAS-4019-CUV	19	0~2.1	±0.5	82	40	200	1.0x2.3x10-L
INPUT	Voltage	(11 ~ 28)VDC						
	Steady DC Current	Maximum steady state input current is less than 10A rms at 11V input and maximum load.						
	Inrush Current	Maximum inrush current shall be less than 6A at 12V DC input.						
	Power Efficiency	82% Min. measured at 11V DC input voltage, maximum load and include the DC cable loss.						
	Connector	Cigarette lighter						
	Input Fuse	No						
OUTPUT	Power ON Led	Yes (Green @ adapter)						
	DC Cable	6A BLACK 1.5M ± 10cm						
PROTECTION	Over voltage protection	The power supply should be protected when output voltage over 15V.						
	Over power protection	The power supply shall be protected when the input DC power protect.						
ENVIRONMENT	Temperature	Operating: (0 ~ 45)°C / Storage: (-20 ~ 85)°C						
	Humidity	Operating: (10 ~ 90)% RH / Storage: (5 ~ 95)% RH non condensing						
	Cooling	The adapter is convention cooled only						
	Insulation Resistance	The resistance is more than 100MΩ at apply 500 VDC between input terminals and Case. The resistance is more than 100MΩ at apply 500 VDC between input terminals and output terminals.						
OTHERS	Case	The case material is PC.Class 94V-0.						
SAFETY		CE						
EMC		EN55022B   FCC Part 15B   CISPR22B   GB9254B   EN61000-4-5 (995+A1: 2001)						
SAFETY		EN60950&60601   UL60905&60601   IEC60950   GB4943						
WEIGHT	1pc	N.W.: 0.127kg / pc   G.W.: 0.176kg/pc						
		0.49 x 0.34 x 0.39 [m]						
PACKING	Box	50pcs / 1box						
		G.W.: 10.5 kg / box						