

Country of Origin : China
 Operating Temperature : 0 ÷ 40[°C]
 Dimension : 70 x 36 x 23 [mm]

Approvals / Marks :



RoHS

Features:

Available as EU and US model
 Light weight. Miniaturization and use of convenience.
 Output connector: USB-A Socket
 Overload, Overvoltage, Short Circuit protection
 For I.T.E use only + RoHS conform.

Specification:

		OUTPUT					
	Model	Voltage DC [V]	min. Load [A]	max. Load [A]	Efficiency [%]	Max. Power [W]	Connector [mm]
	DRKT-0505-W2E	5	0	1	>60	5	USB-A Socket
INPUT	Voltage	(100 ~ 240) VAC					
	Frequency	(50 ~ 60) Hz					
	Current	0.15Amax. @ 230VAC					
	Surge Current	60A @ 230VAC					
	Leakage Current	< 0.25mA					
PROTECTION	Over Load	Yes					
	Over Voltage	Yes					
	Short Circuit	Yes					
OTHERS	Burn in Test	At 40°C a T (±5°C) for 4hrs					
	Resistance Voltage	Yes					
	Connection	Output plug USB A(Socket)					
	M.T.B.F.	> 50K hrs. full load 25°C a T (MIL-HDBK-217F)					
ENVIRONMENT	Temperature	Operating: (0 ~ 40)°C / Storage: (-20 ~ 80)°C					
	Humidity	Operating: 10% ~ 90% RH					
SAFETY		CE TUV/GS CB					
EMC	EMI	FCC Part 15 Class B, AS/NZ S3548/S4251.1 Class B, VCCI Class B, CNS 13438 Class B, GB9254:1998, GB17625.1:2003					
	EMS	EN 55024 A1:2001, EN 61000-4-2/35/6/11					
	Standards	EN60950-1, CE (LVD) TÜV EN60950-1,/A11 :2004 BS EN 60950-:2002					
WEIGHT		N.W.: 48 g/pc G.W.: 59 g/pc					
PACKING	Box	0.41 x 0.35 x 0.18 [m]					
		100pcs / 1box					
		G.W.: 7 kg/box					