


Country of Origin : China
 Operating Temperature : 10 ÷ 40[°C]
 Dimension : 108 x 65 x 31[mm]
 Suitable cable : IEC320-C13 ("PC-Cable")

Approvals / Marks :



Features:

- Single Output, Desktop Adapter with IEC320-C14 Inlet.
- Wide input voltage (100 ~ 240)VAC
- Output voltage available from (5 ~ 30)Vdc in specified steps (OEM section).
- High Performance & compact size
- Applications: Notebook PC / LCD monitor / Printer / HUB / POS / etc.
- Overload & Short circuit protection
- For I.T.E. use only + RoHS conform

Specification - DESKTOP:

	Model	OUTPUT				
		Voltage DC [V]	Load [A]	Tolerance (Load / Line) [%]	Max. Power [W]	Connector [mm]
	DRXX-6012-T3	12	5	5 / 1	60	2.1x5.5x9.5
	DRXX-6024-T3	24	2.5	5 / 1	60	2.1x5.5x9.5
OEM possible OUTPUT	VOLTAGE DC [V]/CURRENT DC[A]	5/6 6/5 9/5 12/3.33 12/4.16 12/5 15/4 16/3.75 18/3.33 19/3.16 20/3 24/2.5 30/2				
INPUT	Voltage	(90 ~ 263) VAC				
	Frequency	(47 ~ 63) Hz				
	Current	max. 1.7A				
PROTECTION	Over Load	Yes				
	Short Circuit	Yes				
OTHERS	Withstand Voltage	I/P-O/P: 1.5KVAC min.				
	Isolation Resistance	I/P-O/P: 500VDC / 50MΩ				
ENVIRONMENT	Temperature	Operating: (10 ~ 40)°C / Storage: (-20 ~ 80)°C				
	Humidity	10% ~ 90% RH				
CONNECTION	Input	IEC 320-C13 ("PC-Cable")				
	Output	It depends on customer's requirements and upon specifications				
SAFETY		Approved: c-UL / TÜV				
EMC		FCC Part 15 Class B / CISPR-22 Class B				
WEIGHT		N.W.: 0.35 kg/pc				
PACKING	Box	0.50 x 0.18 x 0.42 [m]				
		30pcs / 1box				
		G.W.: 10.6 kg/box				