




Country of Origin : China

Operating Temperature : 10 ÷ 40[°C]

Dimension : 117 x 50 x 31[mm]

Suitable cable : IEC320-C5 ("Mickey Mouse")

Approvals / Marks :   

RoHS



### Features:

- Single Output.
- Wide input voltage (100~240)VAC with IEC 320-C5 Inlet.
- Output voltage available from (12~24)VDC in specified steps (OEM section).
- High Performance.
- Compatible with many types of laptops.
- Overload & Short circuit protection.
- For I.T.E. use only + RoHS conform.

### Specification:

		OUTPUT				
	Model	Voltage DC [V]	Load [A]	Tolerance [%]	Max. Power [W]	Connector [mm]
	STTO-7015-M3	15	4.66	5	70	3.0x6.3x11
	STIB-7016-M3	16	4.37	5	70	2.5x5.5x11
	STFS-7016-M3	16	4.37	5	70	4.4x6.0x11
	STHP-7018_5-M3	18	3.88	5	70	5.0x7.4x11
	STCO-7019-M3	19	3.68	5	70	1.7x4.8x11
	STAC-7019-M3	19	3.68	5	70	1.7x5.5x11
	STXX-7019-M3	19	3.68	5	70	2.5x5.5x11
	STXX-7024-M3	24	2.91	5	70	2.1x5.5x11
OEM possible OUTPUT	VOLTAGE / CURRENT [V]DC/[A]DC	12/5   14/5   18.5/3.78   19/3.68   19.5/3.59 20/3.5   22/3.18   24/2.92				
INPUT	Voltage	(100 ~ 240) VAC				
	Frequency	(47 ~ 63) Hz				
	Current	max. 1.5A				
PROTECTION	Over Load	Yes				
	Short Circuit	Yes				
OTHERS	Startup time	-				
	Protective earthing	Class I.				
Environment	Temperature	(10 ~ 40)°C				
	Humidity	5% ~ 95% RH				
Connection	Input	IEC 320-C5 (Or cable IEC230-C6)				
	Output	Connector size depends on customer and upon specifications, 1.8m round cable				
<b>SAFETY</b>		<b>CE   TUV/GS</b>				
EMC		60950-1:2001 + A11:2004; EN55022:1998/A2:2003; EN55024:1998/A2:2003; EN61000-3-2:2000/A2:2005; EN61000-3-3:1995/A2:2005				
WEIGHT		N.W.: 0.29 kg/pc				
PACKING	Box	0.48 x 0.33 x 0.39 [m]				
		50pcs / 1box				
		G.W.: 17 kg/box				