

STXX-120xx-M3

Desktop

120W

Country of Origin : China
Operating Temperature : 10 ÷ 40[°C]
Dimension : 169 x 67 x 41[mm]
Suitable cable : IEC320-C5 ("Mickey Mouse")

Approvals / Marks :



Features:

Single Output
Wide input voltage 100÷240[V]AC with IEC 320-C5 Inlet
Output voltage available from (12÷24)VDC in specified steps
High Performance
Compatible with many types of laptops
Overload & Short circuit protection

Specification - DESKTOP:

| | Model | OUTPUT | | | | |
|---------------------|-------------------------------|---|----------|---------------|----------------|----------------|
| | | Voltage DC [V] | Load [A] | Tolerance [%] | Max. Power [W] | Connector [mm] |
| | STXX-12012-M3 | 12 | 10 | 5 | 120 | 2.1x5.5x11 |
| | STHP-12018_5-M3 | 18.5 | 6.48 | 5 | 120 | 5.0x7.4x11 |
| | STXX-12019-M3 | 19 | 6.31 | 5 | 120 | 2.5x5.5x11 |
| | STSO-12019_5-M3 | 19.5 | 6.15 | 5 | 120 | 5.0x7.4x11 |
| | STXX-12020-M3 | 20 | 6 | 5 | 120 | 2.5x5.5x11 |
| | STXX-12024-M3 | 24 | 5 | 5 | 120 | 2.1x5.5x11 |
| OEM possible OUTPUT | VOLTAGE [V]dc / CURRENT [A]dc | 12/8.75, 14/8.57, 15/8, 16/7.5, 18/6.66, 18.5/6.48, 19/6.31, 19.5/6.15, 20/6, 22/5.45, 24/5 | | | | |
| INPUT | Voltage | (100 ~ 240) VAC | | | | |
| | Frequency | (47 ~ 63) Hz | | | | |
| | Current | max. 2A | | | | |
| PROTECTION | Over Load | Yes | | | | |
| | Short Circuit | Yes | | | | |
| OTHERS | Startup time | - | | | | |
| | Protective class | Class I. | | | | |
| Environment | Temperature | (10 ~ 40)°C | | | | |
| | Humidity | 5% ~ 95% RH | | | | |
| Connection | Input | IEC 320-C5 ("Mickey Mouse") | | | | |
| | Output | It depends on customer and upon specifications | | | | |

SAFETY

| | | |
|---------|-----|---|
| EMC | | 60950-1:2001 + A11:2004; EN55022:1998/A2:2003; EN55024:1998/A2:2003; EN61000-3-2:2000/A2:2005; EN61000-3-3:1995/A2:2005 |
| WEIGHT | | N.W.: 0.69 kg/pc |
| PACKING | Box | 0.48 x 0.33 x 0.39 [m] |
| | | 40pcs / 1box |
| | | G.W.: 32 kg/box |