

# STXX-120xx-M3

# Desktop

# 120W

Country of Origin : China  
Operating Temperature : 10 ÷ 40[°C]  
Dimension : 169 x 67 x 41[mm]  
Suitable cable : IEC320-C5 ("Mickey Mouse")

Approvals / Marks :



### Features:

Single Output  
Wide input voltage 100÷240[V]AC with IEC 320-C5 Inlet  
Output voltage available from (12÷24)VDC in specified steps  
High Performance  
Compatible with many types of laptops  
Overload & Short circuit protection

### Specification - DESKTOP:

	Model	OUTPUT				
		Voltage DC [V]	Load [A]	Tolerance [%]	Max. Power [W]	Connector [mm]
	STXX-12012-M3	12	10	5	120	2.1x5.5x11
	STHP-12018_5-M3	18.5	6.48	5	120	5.0x7.4x11
	STXX-12019-M3	19	6.31	5	120	2.5x5.5x11
	STSO-12019_5-M3	19.5	6.15	5	120	5.0x7.4x11
	STXX-12020-M3	20	6	5	120	2.5x5.5x11
	STXX-12024-M3	24	5	5	120	2.1x5.5x11
OEM possible OUTPUT	VOLTAGE [V]dc / CURRENT [A]dc	12/8.75, 14/8.57, 15/8, 16/7.5, 18/6.66, 18.5/6.48, 19/6.31, 19.5/6.15, 20/6, 22/5.45, 24/5				
INPUT	Voltage	(100 ~ 240) VAC				
	Frequency	(47 ~ 63) Hz				
	Current	max. 2A				
PROTECTION	Over Load	Yes				
	Short Circuit	Yes				
OTHERS	Startup time	-				
	Protective class	Class I.				
Environment	Temperature	(10 ~ 40)°C				
	Humidity	5% ~ 95% RH				
Connection	Input	IEC 320-C5 ("Mickey Mouse")				
	Output	It depends on customer and upon specifications				

### SAFETY

EMC		60950-1:2001 + A11:2004; EN55022:1998/A2:2003; EN55024:1998/A2:2003; EN61000-3-2:2000/A2:2005; EN61000-3-3:1995/A2:2005
WEIGHT		N.W.: 0.69 kg/pc
PACKING	Box	0.48 x 0.33 x 0.39 [m]
		40pcs / 1box
		G.W.: 32 kg/box