

PAA Series

AC-DC Adaptor, 30W-60W

Features

- Single, 30W - 60W, Output
- AC Universal Input, 90Vac - 264Vac
- IEC 320 C6 or C14 Input Receptacle
- Build in CV, CC, CP mode for charger
- Power Saving meet Blue Angle Specs
- High MTBF and High Efficiency design
- OVP, OPP (Auto Recovery), and Short
- Portable, Compact Size with Low Profile
- Multiple Choice of Output Plug and Cable
- Operating Temperature Range 0°C to 40°C
- UL/cUL, TUV, CCC, CB, and more certified



Electrical Specifications

AC Input

- Input Voltage 90 264 VAC
- Input Current 2.5A max.
- Input Frequency 47 63 Hz

- Efficiency 70/80% @ full load, nominal line
- Inrush Current 80A max @ cold start
- Leakage Current 0.75mA max. @ 240Vac input

DC Output 30W-60W Max

Model Number	Power	Voltage	Current	Ripple/Noise	Regulation
PAA030B	30W	5V	6.00A	1%	< 3%
PAA030C	30W	6V	5.00A	1%	< 3%
PAA045E	45W	9V	5.00A	1%	< 3%
PAA040F	40W	12V	3.33A	1%	< 3%
PAA050F	50W	12V	4.16A	1%	< 3%
PAA060F	60W	12V	5.00A	1%	< 3%
PAA060H	60W	15V	4.00A	1%	< 3%
PAA060I	60W	16V	3.75A	1%	< 3%
PAA060J	60W	18V	3.33A	1%	< 3%
PAA060K	60W	19V	3.16A	1%	< 3%
PAA060L	60W	2-V	3.00A	1%	< 3%
PAA060M	60W	24V	2.50A	1%	< 3%
PAA060P	60W	30V	2.00A	1%	< 3%

Mechanical Dimension

- W x L x H = 65 x 108 x 31 mm / 2.56 x 4.25 x 1.22 inch