

Country of Origin : China

Operating Temperature : 10 ÷ 40[°C]

Dimension : 117 x 50 x 31[mm]

Suitable cable : IEC320-C5

Approvals / Marks :



RoHS

### Features:

- Single Output.
- Wide input voltage (100~240)VAC with IEC 320-C5 Inlet.
- Output voltage available from (12~24)VDC in specified steps (OEM section).
- High Performance.
- Overload & Short circuit protection.
- For I.T.E. use only + RoHS conform.

### Specification :

		OUTPUT				
	Model	Voltage DC [V]	Load [A]	Tolerance [%]	Max. Power [W]	Connector [mm]
	STXX-6012-M3	12	5	5	60	2.5x5.5x11
	STUN-6012-M3	12	5	5	60	EBMN <sup>(*)</sup>
	<sup>(*)</sup> DC Connectors		"E" — 4.4 x 6.0 x 11 "B" — 2.1 x 5.5 x 11		"M" — 2.5 x 5.5 x 11 "N" — 4PIN Power DIN	
INPUT	Voltage	(100 ~ 240)VAC				
	Frequency	(47 ~ 63) Hz				
	Current	max. 1.5A				
PROTECTION	Over Load	Yes				
	Short Circuit	Yes				
OTHERS	Startup time	-				
	Protective earthing	Class I.				
Environment	Temperature	(10 ~ 40)°C				
	Humidity	5% ~ 95% RH				
Connection	Input	IEC 320-C5 ("Mickey Mouse")				
	Output	It depends on customer and upon specifications.				
<b>SAFETY</b>						
EMC		60950-1:2001 + A11:2004   EN55022:1998/A2:2003   EN55024:1998/A2:2003 EN61000-3-2:2000/A2:2005   EN61000-3-3:1995/A2:2005				
WEIGHT		N.W.: 0.29 kg/pc				
PACKING	Box	0.48 x 0.33 x 0.39 [m]				
		50pcs / 1box				
		G.W.: 17 kg/box				