

# IEC320-UK series Power cable UK-type

**Possible use in country:**

St. Kitts and Nevis, Guyana, Saudi Arabia, Belize, Bangladesh, St. Vincent and the Grenadines, Vietnam, Yemen, Jordan, Burma(Myanmar), Zambia, Iraq, United Arab Emirates, Pakistan, Singapore, Mauritius, Kuwait, Oman, Channel Islands, Bahrain, Malaysia, Bhutan, Qatar, Tanzania, Ghana, Sierra Leone, Nigeria, Zimbabwe, Dominica, Botswana, Sri Lanka, Macau, Cyprus, Falkland Islands, Gambia, Brunei, Isle of Man, Kenya, Seychelles, Malta, Malawi, Uganda, St. Lucia, United Kingdom, Ireland, Hong Kong, Gibraltar

Cable model: **IEC320-C5 (UK)**

Country of Origin : China

Operating Temperature : 0 ÷ 40[°C]

Length/cord : 1.8m/3x0.75mm<sup>2</sup>

Approvals : ASTA



Application	For Class I. Appliances	
UL Plug	The British Standards 1363 plug (13A Plug) IS 401 and IS 411 (Ireland), MS 589 (Malaysia) and SS 145 (Singapore), and SASO 2203 (Saudi Arabia).	
Fuse	3A/250V	
WEIGHT	1pc	N.W.: 174g / pc
PACKING	Box	0.56 x 0.36 x 0.20 [m]
		90pcs / 1box
		G.W.: 19.7 kg / box



Cable model: **IEC320-C13 (UK)**

Country of Origin : China


Operating Temperature : 0 ÷ 40[°C]

Length/cord : 1.8m/3x0.75mm<sup>2</sup>

Approvals : ASTA



Application	For Class I. Appliances	
UL Plug	The British Standards 1363 plug (13A Plug) IS 401 and IS 411 (Ireland), MS 589 (Malaysia) and SS 145 (Singapore), and SASO 2203 (Saudi Arabia).	
Fuse	5A/250V	
WEIGHT	1pc	N.W.: 195g / pc
PACKING	Box	0.48 x 0.26 x 0.44 [m]
		75pcs / 1box
		G.W.: 12.5 kg / box



Cable model: **IEC320-C7 (UK)**

Country of Origin : China

Operating Temperature : 0 ÷ 40 [°C]

Length/cord : 1.8m/2x0.75mm<sup>2</sup>

Approvals : ASTA



Application	For Class II. Appliances	
UL Plug	The British Standards 1363 plug (13A Plug) IS 401 and IS 411 (Ireland), MS 589 (Malaysia) and SS 145 (Singapore), and SASO 2203 (Saudi Arabia).	
Fuse	5A/250V	
WEIGHT	1pc	N.W.: 120g / pc
PACKING	Box	0.56 x 0.36 x 0.20 [m]
		100pcs / 1box
		G.W.: 14 kg / box

