

Possible use in country:

American Samoa, Anguilla, Antigua, Aruba, Bahamas, Barbados, Bermuda, Bolivia, Cambodia, Canada, Cayman Islands, China, Colombia, Costa Rica, Cuba, Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Guyana, Haiti, Honduras, Jamaica, Japan, Korea North, Korea South, Laos, Liberia, Mexico, Micronesia, Netherlands Antilles, Nicaragua, Niger, Palau, Panama, Peru, Philippines, Puerto Rico, St. Vincent (Windward Islands), Saudi Arabia, Taiwan, Thailand, Trinidad & Tobago, Turks and Caicos Islands, United States of America, Venezuela, Vietnam, Virgin Islands, Yemen.

Cable model: **IEC320-C5 (UL)**

Country of Origin : China

Operating Temperature : 0 ÷ 40 [°C]

Length/cord : 1.8m/3x0.75mm

Approvals : UL



Application	For Class I. Appliances	
UL Plug	American standard NEMA 5- Canadian standard CS22.2, n°42	
WEIGHT	1pc	N.W.: 72g / pc
		. x 0. x 0. [m]
PACKING	Box	pcs / 1box
		G.W.: 16kg / box

Cable model: **IEC320-C13 (UL)**

Country of Origin : China

Operating Temperature : 0 ÷ 40[°C]

Length/cord : 1.8m/3x0.75mm

Approvals : UL



Application	For Class I. Appliances	
UL Plug	American standard NEMA 5- Canadian standard CS22.2, n°42	
WEIGHT	1pc	N.W.: 72g / pc
		. x 0. x 0. [m]
PACKING	Box	pcs / 1box
		G.W.: 12.5 kg / box

Cable model: **IEC320-C7 (UL)**

Country of Origin : China

Operating Temperature : 0 ÷ 40 [°C]

Length/cord : 1.8m/2x0.75mm

Approvals : UL



Application	For Class II. Appliances	
UL Plug	American standard NEMA 1-15	
WEIGHT	1pc	N.W.: 72g / pc
		. x 0. x 0. [m]
PACKING	Box	pcs / 1box
		G.W.: 15.5 kg / box

